

Index to the information package of a type approval with regard to a Regulation (UNECE) :

Last applicable Series of amendments	Base approval and update No	Extension No	Revision No	Issue date	Information document	
					Reference	Number of pages
R58-03	00	---	---	Signature date	TDHRUP211213T1	61

Approved and to be attached to the approval certificate,



R. VERHELST

Getekend op : 2022-06-30 10:34:26 +0200 te Brussel

dossier nr. 43362 - E6\*58R03/02\*0743\*00





Communication concerning :

- Approval granted <sup>(1)</sup>
- ~~Approval extended <sup>(4)</sup>~~
- ~~Approval refused <sup>(4)</sup>~~
- ~~Approval withdrawn <sup>(4)</sup>~~
- ~~Production definitively discontinued <sup>(4)</sup>~~

of a type of rear underrun protective device (RUPD), pursuant to Regulation No.58

Approval No : E6\*58R03/02\*0743\*00

Extension No : 00

1. Trade name or mark of device : ALMIC
2. Type of device : BU
3. Name and address of manufacturer : ALMIC BV  
Bosuilstraat 7  
B-3910 Pelt (Neerpelt)
4. If applicable, name and address of the manufacturer's representative : -
5. Characteristics of the device (dimensions and its fixing elements) : See information folder
6. Test conducted on a vehicle / on a representative part of the chassis of a vehicle <sup>(1)</sup>.
7. Position on the device of the points of application of the test forces : P1: 975 mm from the middle  
P2: 350 mm from the middle  
P3: 0 mm from the middle
8. Maximum horizontal and vertical deflection observed during and after the application of the test forces in Annex 5 : During:  
Horizontal: 110mm  
Vertical: 180mm downwards  
After:  
Horizontal: 19mm  
Vertical: 34mm downwards
9. Restrictions on application  
  
Vehicles on which the device may be installed (if applicable) : See information folder  
  
Characteristics of the chassis to which the device may be installed (e.g. stiffness, profile dimensions, ...) (if applicable) : See information folder
10. Maximum mass of vehicle on which the device may be installed : Unlimited
11. Device submitted for approval on : 24/06/2022

Getekend op : 2022-06-30 10:34:26 +0200 te Brussel

dossier nr. 43362 - E6\*58R03/02\*0743\*00



12. Technical Service responsible for conducting approval tests: ESTL NV  
Wafelstraat 46  
8540 Deerlijk  
Belgium
13. Date of report issued by that service: 24/06/2022
14. Number of report issued by that service : HRUP211213T1
15. Approval has been granted / ~~refused~~ / ~~extended~~ / ~~withdrawn~~ in respect of the RUPD <sup>(1)</sup>
16. Position of approval mark on the device : on the top side of the main transverse beam
17. Place : Brussels
18. Date : Signature date
19. Signature :

ON BEHALF OF THE SECRETARY-GENERAL:



R. VERHELST

20. The following documents, bearing the approval number shown above, are available upon request:
- Drawings, diagrams and layout plans of the components of the structure considered to be of importance for the purposes of this Regulation;
  - Detailed information about the devices representing the vehicle structures used for the mounting of the RUPD (e.g. moment of inertia of the beams);
  - Where applicable drawings of the protective devices and their position on the vehicle.

(1) *Delete where not applicable*





**ESTL nv**  
Wafelstraat 46 -B 8540 Deerlijk  
**Automotive certification**  
homologation@estl.be

www.estl.be  
BTW 0818.634.666  
+32 (0) 56 77 86 00






<b>1. Report</b>	No.:	<b>HRUP211213T1</b>	Update:	00
	Ref.:	-	Annexes:	See Part 6.

<b>2. Test Subject</b>	Rear Underrun Protection Devices ( RUPDs) - Part I		
According to:	ECE R58-03	Supplement 2	EC 661/2009

<b>3. Information</b>	
Manufacturer:	Almic BV Bosuilstraat 7 3910 Pelt Belgium
Make of the RUPD:	ALMIC
Type of the RUPD:	BU
Variants:	M: Mechanical
Version:	450; 650; 850; 1050
Commercial description:	/
Category(ies) :	O, N

<b>4. Test</b>		
Place and date:	ESTL, Wafelstraat 46, Deerlijk, Belgium	14/02/2022
Manufacturer's representative:	M. Marc Janssens	
Test Engineer:	Ing. Kristof Baeyens en ing. Jeroen D'Haese	
Technical documentation:	TDHRUP211213T1	
Location of E-mark:	on the top side of the main transverse beam	

<b>5. Conclusions</b>	
The model represented fulfills the hereunder performed tests, as described in Regulation 58-03.	
Performed by:	Revised by:
 Ing. Kristof Baeyens en ing. Jeroen D'Haese Test Engineer	 Ing. Kristof Baeyens Homologation manager
Date:	24/06/2022



Report type :	Base report / Extension / Revision
Reason for extension / revision :	-
Scope for approval :	Individual / National series / International series
Test subject & scope:	BUM; 450 ; 650; 850; 1050

### Part 1: Information test specimen

Make of the RUPD:	ALMIC
Type of the RUPD:	BU
Commercial description:	/
Category(ies) :	O, N
Possible Variants:	
Sample reception date:	14/02/2022
Worst case evaluation:	The system is tested at : *smallest/largest chassis width. *highest support length. *widest length. *smallest chassis inertia moment *Longest version of 1050mm *The manual mechanical actuation system is tested.

### Part 2: General specifications

Par.	Subject	Result
5.2	The application for EU type-approval shall be accompanied by an information form, with detailed technical characteristics: *dimensions, and constituent materials *method of installation	Complies

### Part 3: Individual specifications

#### 3.0 General specifications

Par.	Subject	Result
7.1	The cross-member shall have a section height of at least 120 mm. The lateral extremities of the cross member shall not bend to the rear or have a sharp outer edge; this condition is fulfilled when the lateral extremities of the cross-member are rounded on the outside and have a radius of curvature of not less than 2.5 mm.	Complies
	RUPD intended to be fitted on vehicles of categories M, N1, N2 with a maximum mass not exceeding 8 t, O1, O2, on vehicles of category G and on vehicles fitted with a platform lift, the cross-member shall have a section height of at least 100 mm.	Not appl.
7.2	The RUPD may be so designed to have several positions at the rear of the vehicle. In this event, there shall be a guaranteed method of securing it in the service position so that any unintentional change of position is precluded. The force applied by the operator to vary the position of the device shall not exceed 40 daN.	Complies
	For RUPD that are designed to have several positions at the rear of the vehicle, a label shall be provided either with (a) symbol(s) or in the language(s) of the country where the device is sold to inform the operator about the standard position of the RUPD to offer effective protection against under-running. Label minimum size: 60x120mm	Complies

7.3	The RUPD shall offer adequate resistance to forces applied parallel to the longitudinal axis of the vehicle. (This shall be demonstrated in accordance with the test procedure and test conditions specified in Annex 5 to this Regulation.) The maximum horizontal deflection of the RUPD observed during and after the application of the test forces specified in Annex 5 shall be recorded on the type approval communication (Annex 1, item 8).	Complies
7.4	For vehicles fitted with a platform lift at the rear, the underrun device may be interrupted for the purposes of the mechanism. In this case, the following special requirements apply:	
7.4.1	The maximum lateral clearance measured between the elements of the underrun device and the elements of the platform lift, which move through the interruption when the lift is operated and which make the interruption necessary, may amount to no more than 2.5 cm.	Not appl.
7.4.2	The individual elements of the underrun protection, including those outboard of the lift mechanism, where provided, must have an effective surface area, in each case, of at least 420 cm <sup>2</sup> .	Not appl.
7.4.3	For cross-members with a section height of less than 120 mm, the individual elements of the underrun protection, including those outboard of the lift mechanism, where provided, shall have an effective surface area, in each case, of at least 350 cm <sup>2</sup> .	Not appl.
7.4.4	In the case of vehicles having a width of less than 2,000 mm and where it is impossible to achieve the requirements of paragraphs 7.4.2. and 7.4.3., the effective surface may be reduced on the condition that the resistance criteria are met.	Not appl.

### 3.1 Dimensional specifications

Par.	Dimension	Value	
	Wider rear axle width	2550	mm
	Cross-member width	2350	mm
	Transverse distance between brackets: min	760	mm
	Transverse distance between brackets: max	860	mm
	Difference in transverse distance	100	mm
	Width difference on the left side (≤100mm)	100	mm
	Width difference on the right side (≤100mm)	100	mm

## Part 4: Physical test

### 4.0 Test method

A5 1.4	If the cross-member does not have a vertical flat surface of at least 50 % of the minimum section height at the test force height, a device that doesn't modify the dimensional and mechanical characteristics of the RUPD or increase its resistance is used. The device shall neither be rigidly fixed to the RUPD nor to the test equipment.	Complies
A5 1.3	The test procedure may be simulated by calculation. A validation report shall be drafted by the manufacturer or by the technical service and submitted to the Type Approval Authority.	Not appl.

A. Rigid test bench	Complies	
A5 1.1.2	RUPD is tested <del>calculated</del> on a rigid test bench.	Complies

A5 1.2	RUPD is tested on a test bench with a part of chassis of the vehicle type. The parts used to connect the RUPD to the vehicle chassis shall be equivalent to those which are used to secure the RUPD when it is installed on the vehicle. The distance of the foremost fixing point of the RUPD from the rigid test bench shall not be less than 500 mm.	Complies
--------	---	----------

B. Vehicle test		Not appl.
A5 2.1	The vehicle shall be at rest on a level, flat, rigid and smooth surface.	Not appl.
A5 2.2	The front wheels shall be in the straight-ahead position.	Not appl.
A5 2.3	The tyres shall be inflated to the pressure recommended by the vehicle manufacturer.	Not appl.
A5 2.4	The vehicle may, if necessary to achieve the test forces required in § 3.1. below, be restrained by any method.	Not appl.
A5 2.5	Vehicles equipped with hydropneumatic, hydraulic or pneumatic suspension or a device for automatic levelling according to load shall be tested with the suspension or device in the normal running condition specified by the manufacturer.	Not appl.

#### 4.1 Chassis

Minimal moment of inertia of chassis members (one chassis beam) [mm <sup>4</sup> ]	57080000
--	----------

#### 4.2 Height regulation device test

7.2	If the RUPD is designed to have several positions at the rear of the vehicle, there must be a guaranteed method of securing it in the service position so that any unintentional change of position is precluded. Force applied by the operator to change position ≤ 40 daN.	<40	daN
7.2	Aa label shall be provided either with (a) symbol(s) or in the language(s) of the country where the device is sold to inform the operator about the standard position. Label min. size: 60 x 120 mm	Complies	

#### 4.3 Load test dimensions

Par.	Point	Horizontal transverse position	
A5 3.1.2	P1	975	mm from the middle
A5 3.1.3	P2	350	mm from the middle
A5 3.1.1	P3	0	mm from the middle
	Point	Vertical position	
	P1; P2; P3	60	mm above the underside of the device (ground clearance reference plane)

#### Informative

A5 3.2.1	Replacement force if point in interruption area (Platform lift) * P2: replacement point: within 50mm to the intended points * P1: replacement point: max. 325mm from outer edges of the wheels on the rear axle
	Test point height ≤600mm above the ground. (If tested on a vehicle)

#### 4.4 Load test forces

Techn. perm. maximum mass vehicle:	Unlimited	kg
If special vehicle: 80% of nominal value [A5 §3,1,3]	100	%

Point (from left to right)	Specified Load A5 §3 [daN]	Max. Applied Load [daN]	Deflection [mm]			
			Horizontal		Vertical	
			During	After	During	After
Manual mechanical system						
Point P1	0	10010	110	19	153	34
Point P2	0	18015	103	19	180	31
Point P3	0	10020	17	2	34	3
Point P2	0	18020	76	15	151	27
Point P1	0	10030	95	9	125	13
Direction of deflection					Downwards	

Remark: -Tested from left to right

#### 4.5 Result

7.3	Max. deflection [mm] A1 Pt. 8	Horizontal		Vertical	
		During	After	During	After
		110	19	180	34

#### Part 5: Conclusions and remarks

-The dimensional requirements are to be evaluated after installation.  
-material specs are declared by manufacturer and not checked.

#### Part 6: Annexes

No.	Description	# Pages
-	-	-

#### Part 7: Used test equipment

Description	Registration number	Calibrated	Applicable
Length meter	T_LMT_5m_05	x	x
Force controller	UTMC_02 MCIL_D60100450_01	x	x
Load cell	LC_99K_01	x	x
Digital angle meter	T_DHM_08	x	x
Digital protractor	T_DSMM_05	x	x
Radius caliper	CAL_R2,5_01	x	x
Displacement measurement device	T_LTK_1.25m_04&05	x	x